



VIPULORGANICS

Interconnected Chemistry

SunTONE[®]

Pigments For Paint

Colours that
make you happy.



	SunTONE® Product Code	Pigment/ Colour Index No.	Specific Gravity	Oil Absorption ml. / 100g	Fastness Properties						Bleeding Resistance							Application			
					Light Fastness		Weather Fastness		Acid Resistance	Alkali Resistance	Heat Resistance	Water	Ethyl Alcohol	Ethyl Acetate	Xylene	M.E.K.	Mineral Spirit	Paint		Textile	Rubber
					Full Tone	Tint Tone	Full Tone	Tint Tone										Solvent Base	Water Base		
	Yellow 303	PY 1	1.40	≤45	7	4-5	3	2	5	5	160	5	4	3	3	3	4	●	●	●	
	Yellow 305 C	PY 1	1.40	≤45	7	4-5	4	3	5	5	160	5	4	3	3	3	4	●	●		
	Yellow 309	PY 3	1.55	≤45	7	6	3	2	5	5	160	5	3-4	4	3-4	4	4		●	●	
	Yellow 3361	PY 12	1.40	≤50	4-5	3	3	2	5	5	180	5	4-5	3-4	3	3-4	5	●	●	●	
	Yellow 3195	PY 65	1.50	≤55	7-8	6-7	4	3	5	5	160	5	4-5	4	4-5	2	5	●	●	●	
	Yellow 3221	PY 74 (2GX)	1.70	≤45	7	5-6	4	2	4	4	180	5	5	4	3	4	5	●	●	●	
	Yellow 3222	PY 74 (5GX)	1.60	≤45	7	5-6	4	2	4	4	180	5	4	3	3	3	4	●	●	●	
	Yellow 3223	PY 74 (5GX)	1.60	≤45	7	5-6	4	2	4	4	180	5	4	3	3	3	4	●	●	●	
	Yellow 3249	PY 83	1.55	≤45	7	5-6	4	3	4-5	4-5	240	5	3-4	3	3	3	5	●	●	●	●
	Yellow 3251 C	PY 83	1.70	<55	7-8	5-6	5	3	4-5	4-5	220	5	4	4	4	4	5	●	●		
	Yellow 3414	PY 138	1.80	≤40	7	7	5	4	5	5	250	5	4-5	5	3-4	3-4	5	●	●		
	Yellow 3417	PY 139	1.60	≤50	7-8	7	5	4	5	5	240	5	5	5	5	5	5	●	●		●
	Yellow 3453	PY 151	1.60	≤65	7	6-7	5	4	5	5	280	5	5	5	5	5	5	●	●		●
	Yellow 3462	PY 154	1.65	≤55	8	6-7	5	4	5	5	280	5	5	5	4	4	4	●	●		●
	Orange 735	PO 5	1.30	<40	7	6	4	3	5	5	160	5	4	3-4	4	3-4	3-4		●	●	
	Orange 791	PO 13	1.50	≤50	7	5-6	3	2	5	3	240	5	3-4	4	3	3-4	4	●	●	●	●
	Orange 7238	PO 34	1.30	≤40	6	5	4	3	4	5	180	4	4	3	3	5	5	●	●	●	●
	Orange 7252	PO 36	1.30	≤40	8	6-7	5	4	5	5	280	5	5	5	5	5	5	●	●		●
	Orange 7448	PO 64	1.55	≤60	8	8	4	3	5	5	280	5	4-5	5	5	5	5	●	●		
	Red 515	PR 3	1.40	≤50	7	4-5	3	2	5	5	180	5	3	3	2-3	2	3-4	●	●	●	
	Red 516	PR 3	1.40	≤50	7	4-5	3	2	5	5	180	5	3	3	2-3	2	3-4	●	●	●	
	Red 520	PR 4	1.50	≤45	6	5	3	2	3	3	160	4	3	3	2	2	4	●	●	●	
	Red 525	PR 5	1.50	≤55	7	5	3	2	5	5	200	5	4	4	3-4	3	3-4	●	●		
	Red 540	PR 8	1.60	≤55	5-6	4	3	2	5	4	180	5	3	3	2	3	4	●	●	●	
	Red 560	PR 12	1.50	≤55	6	4-5	3	2	4	4	160	3	3	3	2-3	2-3	3-4	●	●	●	
	Red 5241	PR 48.2	1.40	≤59	6-7	6	3	2	4	4	260	4	4-5	3-4	4-5	4-5	4-5	●	●		
	Red 5247	PR 48.4	1.40	≤59	6-7	6	4	3	4	4	260	4	4-5	3-4	4-5	4-5	4-5	●	●		

	SunTONE® Product Code	Pigment/ Colour Index No.	Specific Gravity	Oil Absorption ml. / 100g	Fastness Properties						Bleeding Resistance							Application			
					Light Fastness		Weather Fastness		Acid Resistance	Alkali Resistance	Heat Resistance	Water	Ethyl Alcohol	Ethyl Acetate	Xylene	M.E.K.	Mineral Spirit	Paint		Textile	Rubber
					Full Tone	Tint Tone	Full Tone	Tint Tone										Solvent Base	Water Base		
	Red 5285 C	PR 57.1	1.50	≤55	5	3	3	2	3	2	200	5	4	3	3	3	4	●			
	Red 5315	PR 63.1	1.50	≤55	6	4-5	3	2	3	3	160	5	4	4	5	3	4	●	●	●	
	Red 5560	PR 112	1.50	≤40	7	6	3	2	5	5	200	5	4	5	5	5	5	●	●	●	
	Red 5561	PR 112	1.50	≤40	7	6	3	2	5	5	200	5	4	5	5	5	5	●	●	●	
	Red 5562	PR 112	1.50	≤40	7	6	3	2	5	5	200	5	4	5	5	5	5	●	●	●	
	Red 5563	PR 112	1.50	≤40	7	6	3	2	5	5	200	5	4	5	5	5	5	●	●	●	
	Red 5610	PR 122	1.50	≤45	7-8	6	5	5	5	5	280	5	4-5	5	5	5	5	●	●	●	●
	Red 5730	PR 146	1.40	≤50	6	4-5	3	2	4	5	180	5	4	4	3	4	5	●	●	●	
	Red 5850	PR 170	1.45	≤50	7	6	4	2	5	5	260	5	4-5	4	4	4	5	●	●	●	
	Red 5851	PR 170	1.50	≤50	7	6	5	4	5	5	260	5	4-5	4-5	4-5	4	5	●	●		●
	Red 5940	PR 188	1.50	≤50	7-8	7	4	3	5	5	200	5	4	4	4	4	4	●	●		
	Red 51190	PR 238	1.60	≤45	5	4	3	2	4	5	180	5	4	4	4	4	4	●	●	●	
	Red 51270	PR 254	1.40	≤50	8	7	5	5	5	5	260	5	5	5	5	5	5	●	●		
	Green 107	PG 7	1.60	≤45	8	7	5	5	5	5	280	5	5	5	5	5	5	●	●	●	●
	Green 108	PG 8	1.50	≤45	6	5	3	2	5	5	180	5	4	4	3	4	4	●	●	●	●
	Blue 9150	PB 15.0	1.50	≤45	8	7	5	5	4	5	220	5	5	5	4-5	4-5	5	●	●	●	●
	Blue 9153	PB 15.3	1.40	≤50	8	7	5	5	5	5	280	5	5	5	5	5	5	●	●	●	●
	Blue 9261	PB 29	5.6	≤30	4	3-4	4	3	4	3-4	230	4	4	4	4	4	4	●	●		●
	Violet 1119	PV 19	1.40	≤50	8	7-8	5	4	5	5	260	5	5	5	5	5	5	●	●	●	
	Violet 1123	PV 23	1.40	≤50	7	6	5	4	5	5	260	5	5	5	5	5	5	●	●	●	
	Violet 1124	PV 23	1.40	≤50	7	6	5	4	5	5	260	5	5	5	5	5	5	●	●	●	
	Yellow 2222	PY 34	5.10	≤30	7-8	6-7	5	4	5	5	220	5	5	5	5	5	5	●	●		
	Yellow 2232	PY 34	5.40	≤30	7-8	6-7	5	4	5	5	220	5	5	5	5	5	5	●	●		
	Orange 4245	PR 104	6.00	≤30	7-8	6-7	5	4	2-3	4	230	5	5	5	5	5	5	●	●		
	Yellow NM	Organic Lemon Chrome	1.60	≤45	7	5-6	4	3	4	4	160	5	4	3	3	3	4	●	●		
	Yellow MV	Organic Middle Chrome	1.50	≤55	7-8	6-7	4	3	5	4-5	160	5	4-5	4	4-5	2	5	●	●		
	Scarlet JP	Organic Scarlet Chrome	1.30	<45	6	5	4	3	4	4	180	5	4	4	3	3	5	●	●		●

Light Fastness Scale : 1 - 8, 1 is Poor & 8 is Excellent • Weather Fastness Scale : 1 - 5, 1 is Poor & 5 is Excellent

Vipul Organics was established in the year 1968. We are one of the fastest growing companies in the manufacturing of Pigments and Pigment Dispersions. We have four manufacturing facilities which function at the highest quality and operations level, following systems such as ISO 9001:2015. Our head office is in Mumbai. With presence in 45 countries, **Vipul Organics**, is a global color solution provider.

SunTONE® range of pigments includes classical Azo Pigments, Phthalocyanines and some High performance pigments for the Paint, Ink, Plastic, Textile and Rubber industry. Over the years, we have invested substantially in R&D and Applications Service to develop new products and support the evolving needs of our customers.

Our pigments have been carefully formulated to provide a wide range of palette of colors for decorative paints and coatings.

We also have REACH Registered Pigments.

Technical properties :

- Wide range of vibrant opaque, translucent and transparent pigments
- Good Rheology which allows high pigment loading during milling
- Bright and Intense Colors
- Good Light and Weather fastness
- Good Solvent and Bleed Fastness
- Easily dispersible Colors
- Good compatibility with solvent and water based paints

Disclaimer : The information included here is based on the reliable data generated by our laboratories. Since the Performance of a pigment also depends on the additives and polymers used, we recommend that customers should test the suitability of the pigment for their end application. However, if we are provided with testing methods and samples, we would be glad to do the same.


Caution: We do not recommend that any of our products are used in sensitive applications which may come in contact with internal body organs or body fluids.

Color Reproduction : The colors above have been generated electronically and should therefore not be used for comparison purposes. The colors are meant to give a first impression of the colorant shade.


Pigments for Ink




Pigments for Plastic



Pigment Dispersions for Paint & Coating



Pigment Dispersions for Textile Printing



Vipul Organics Ltd., 102, Andheri Industrial Estate, Off Veera Desai Road, Andheri (W), Mumbai 400053, India

+91 22 6613 9999 | +91 22 6613 9977 / 75 | marketing@vipulorganics.com | www.vipulorganics.com | www.facebook.com/VipulOrganics



PALGHAR | AMBERNATH | AHMEDNAGAR | NAVI MUMBAI | TARAPUR | DAHEJ